

General Description

The AOZ8331DI-05 is a single channel bidirectional high surge transient voltage suppressor designed to protect data lines such as audio line and power rail from damaging ESD or surge events.

This device consists of a bidirectional TVS diodes in a single package. During transient conditions, the bidirectional diodes direct the transient to either the positive side of the power supply line or to ground.

The AOZ8331DI-05 provides a typical capacitance of 55 pF and low clamping voltage making it ideally suited for data transmission protection in mobile and computing devices.

The AOZ8331DI-05 comes in a RoHS compliant and Halogen Free 1.0 mm×0.6 mm×0.5 mm package and is rated for -40°C to +125°C junction temperature range.

Features


- ESD protection for high-speed data lines:
 - IEC 61000-4-2, ESD immunity:
 - Air discharge: ±30kV
 - Contact discharge: ±30kV
 - IEC 61000-4-5 (Lightning, 8/20µs) 35A
- Capacitance between I/O to GND: 55 pF
- Low clamping voltage
- Low operating voltage: 5.5 V

Applications


- Audio lines
- 5V Power Rail
- Mobile Phone
- Notebook Computers



Typical Application



Pin Configuration



DFN1.0x0.6_2L

Ordering Information

Part Number	Ambient Temperature Range	Package	Environmental
AOZ8331DI-05	-40°C to +125°C	DFN1.0 x0.6-2L	Green Product



AOS Green Products use reduced levels of Halogens, and are also RoHS compliant.
Please visit www.aosmd.com/media/AOSGreenPolicy.pdf for additional information.

Absolute Maximum Ratings

Exceeding the Absolute Maximum ratings may damage the device.

Parameter	Rating
Storage Temperature (T _S)	-65°C to +150°C
ESD Rating per IEC61000-4-2, contact ⁽¹⁾	±30kV
ESD Rating per IEC61000-4-2, air ⁽¹⁾	±30kV
8/20µs Surge IEC61000-4-5	±35A

Notes:


- IEC 61000-4-2 discharge with C_{Discharge} = 150pF, R_{Discharge} = 330Ω.
- Human Body Discharge per MIL-STD-883, Method 3015 C_{Discharge} = 100pF, R_{Discharge} = 1.5kΩ.

Maximum Operating Ratings

Parameter	Rating
Junction Temperature (T _J)	-40°C to +125°C

Electrical Characteristics

T_A = 25°C unless otherwise specified.



Symbol	Parameter	Conditions	Min.	Typ.	Max.	Units
V _{RWM}	Reverse Working Voltage				5.5	V
V _{BR}	Reverse Breakdown Voltage	I _T =1mA	6	7.5	9	V
I _R	Reverse Leakage Current	V _T =Max. V _{RWM}		0.1	100	nA
V _{HOLD}	Hold Voltage of Snapback ⁽³⁾	I _T =100mA	5.0			V
V _{CL}	Clamping Voltage ⁽³⁾⁽⁴⁾ (100ns Transmission Line Pulse)	I _{TLP} =1A		6.5	8	V
		I _{TLP} =16A		7.5	9	
		I _{TLP} =30A		8.5	10	
R _{DNY}	Dynamic Resistance ⁽³⁾	I _{TLP} =1 to 30A		0.07		Ω
V _{CL}	Clamping Voltage ⁽³⁾ IEC61000-4-5 Surge 8/20μs	I _{PP} =2A		6.3	7.6	V
		I _{PP} =30A		10.5	12	
C _J	Junction Capacitance	V _{IO} = 0V, f = 1MHz		55	75	pF


Note:

- 3. These specifications are guaranteed by design and characterization.
- 4. Measurements performed using a 100ns Transmission Line Pulse (TLP) system.


Typical Characteristics

$T_A = 25^\circ\text{C}$, $V_{IN} = 5\text{V}$ unless otherwise specified.


Typical Variations of CJ vs. Input Voltage




Positive Transmission Line Pulse
($t_p=100\text{ns}$, $t_r=0.2\text{ns}$, Pin1 to Pin2)





IEC61000-4-5 Surge 8/20us




Negative Transmission Line Pulse
($t_p=100\text{ns}$, $t_r=0.2\text{ns}$, Pin1 to Pin2)



Package Dimensions, DFN1.0x0.6-2L, EP2_S



RECOMMENDED LAND PATTERN




UNIT: mm

SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.47	0.50	0.53	0.019	0.020	0.021
A1	0.00	0.03	0.05	0.000	0.001	0.002
b	0.45	0.50	0.55	0.018	0.020	0.022
D	0.95	1.00	1.05	0.037	0.039	0.041
E	0.55	0.60	0.65	0.022	0.024	0.026
e	---	0.40	---	---	0.016	---
L	0.20	0.25	0.30	0.008	0.010	0.012
L1	0.05±0.03 Ref.			0.002±0.001 Ref.		
R	0.05	0.10	0.15	0.002	0.004	0.006
aaa	0.15			0.006		
bbb	0.05			0.002		
ccc	0.05			0.002		

NOTE


1. ALL DIMENSION ARE IN MILLIMETERS.ANGLES ARE IN DEGREES.
2. COPLANARITY APPLIES TO THE EXPOSED HEAT SINK SLUG AS WELL AS THE TERMINALS.
3. THE SHAPE OF PIN ID CAN BE DIFFERENT PER MANUFACTURING LOCATION

Tape and Reel Dimensions, DFN1.0x0.6-2L, EP2_S



PACKAGE	A0	B0	K0	D0	D1	E	E1	E2	P0	P1	P2	T
DFN1.0x0.6/ DFN1.0x0.6A (8 mm)	0.65 ±0.04	1.05 ±0.04	0.61 ±0.04	0.40 ±0.05	1.50 +0.10	8.00 +0.30 -0.10	1.75 ±0.10	3.50 ±0.05	2.00 ±0.10	4.00 ±0.10	2.00 ±0.05	0.20 ±0.05

Reel




TAPE SIZE	REEL SIZE	M	N	W	W1	H	K	S	G	R	V
8 mm	ø178	ø178 ±0.5	ø55 ±1	8.4 +1.5 -0.5	MAX. 14.4	ø13.0 ±0.5	MAX. 10.1	2.0 ±0.5	N/A	N/A	N/A

Tape

Leader / Trailer
& Orientation


TVS

Unit Per Reel:
10000pcs



DETAIL:
UNIT DIRECTION IN POCKET

Part Marking



LEGAL DISCLAIMER

Applications or uses as critical components in life support devices or systems are not authorized. AOS does not assume any liability arising out of such applications or uses of its products. AOS reserves the right to make changes to product specifications without notice. It is the responsibility of the customer to evaluate suitability of the product for their intended application. Customer shall comply with applicable legal requirements, including all applicable export control rules, regulations and limitations.

AOS' products are provided subject to AOS' terms and conditions of sale which are set forth at:

http://www.aosmd.com/terms_and_conditions_of_sale

LIFE SUPPORT POLICY

ALPHA AND OMEGA SEMICONDUCTOR PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS.

As used herein:

- | | |
|---|---|
| <p>1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.</p> | <p>2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.</p> |
|---|---|