

ESD TEST REPORT

Human Body Model

JS-001-2017

ANSI/ESDA/JEDEC Standard, Method JS-001-2017 is an ESD test using Human Body Model where "R = 1500 ohm", "C = 100pf", one positive and one negative pulses applied to the devices per customer's specification with a minimum of 0.1 second cool down between pulses.

Customer : Chongqing Alpha and Omega Semiconductor Limited

Address: No. 288 Yuefu Road, Beibei District, Chongqing, P.R. China

Device Information

Part No. :	AOC3860C	Sample Size :	8pcs
Package Type :	MCSP3.05*1.77	Pin Count :	6
Lot No. :	9C03	Date Code :	-
VDD Domains :	S2 S1	VSS Domains :	S1 S2

Test Equipment

Tester :	ZAPMASTER MK.2 SE	Serial No. :	0508317
Calibration Date :	Jun 20 th 2019	Expiration Date :	Jun 19 th 2020

Environmental Condition

Temperature :	23°C	Humidity :	50% RH
Submit date :	Jan 20 th 2020	Complete date :	Jan 20 th 2020

Stress Summary

Channel_1 G1 TO S1			
Sample No.	Stress Type	Voltage Level	Spot Test Results* (Within 10μA @ 8V between G1 and S2/S1)
1#	HBM	-3.2kV	FAILED
2#	HBM	±3.1kV	PASS
3#	HBM	±3.1kV	PASS
4#	HBM	±3.1kV	PASS

Channel_1 G1 TO S2			
Sample No.	Stress Type	Voltage Level	Spot Test Results* (Within 10μA @ 8V between G1 and S2/S1)
5#	HBM	+3.4kV	FAILED
6#	HBM	±3.3kV	PASS
7#	HBM	±3.3kV	PASS
8#	HBM	±3.3kV	PASS


Channel_2 G2 TO S2			
Sample No.	Stress Type	Voltage Level	Spot Test Results* (Within 10μA @ 8V between G2 and S1/S2)
1#	HBM	-3.3kV	FAILED
2#	HBM	±3.2kV	PASS
3#	HBM	±3.2kV	PASS
4#	HBM	±3.2kV	PASS

Channel_2 G2 TO S1			
Sample No.	Stress Type	Voltage Level	Spot Test Results* (Within 10µA @ 8V between G2 and S1/S2)
5#	HBM	-3.3kV	FAILED
6#	HBM	±3.2kV	PASS
7#	HBM	±3.2kV	PASS
8#	HBM	±3.2kV	PASS

Test Result*

Model	Pin Combinations	ESD Sensitivity Pass*: 3.1kV	V Class
HBM	Channel 1 – G1 vs. S1	±3.1kV	2 JS-001-2017 Class 0Z: <50V Class 0A: 50V~124V Class 0B: 125V~249V Class 1A: 250V~499V Class 1B: 500V~999V Class 1C: 1000V~1999V Class 2: 2000V~3999V Class 3A: 4000V~7999V Class 3B: ≥8000V
	Channel 1 – G1 vs. S2	±3.3kV	
	Channel 2 – G2 vs. S2	±3.2kV	
	Channel 2 – G2 vs. S1	±3.2kV	

*Note: Results will be updated based on customer final electrical test results.

Test Engineer: Fei Teng	Date: Jan 20 th 2020
Approved by FA Manager: 	Date: Jan 20 th 2020



Recommendations

EAG Shanghai certifies that above tests have been performed in accordance to the requirements stated above and per the customer purchase order and applicable documents.

EAG Shanghai recommends electrical testing as a validation of reported results. Curve Trace criteria was utilized to specify a pass or fail. Industry standards require the device to be tested functionally at post stress and should continue to meet all electrical parameters as per the data sheet.

This report can not be duplicated in part, without the permission of EAG Shanghai. This report refers only to the specimen(s) submitted to test, and is invalid if used separately. This report is only valid with the examination seal and signature of EAG Shanghai. The tested specimen(s) will only be preserved for thirty days form the date issued, if not collected by the applicant. If discrepancies exist about report, please put forward within one week.