



**ALPHA & OMEGA**  
SEMICONDUCTOR

**AOTL66811**  
**80V N-Channel AlphaSGT2™**

### General Description

- AlphaSGT2™ N-Channel Power MOSFET
- Low  $R_{DS(ON)}$
- Low Gate Charge
- Enhanced body diode performance
- RoHS 2.0 and Halogen-Free Compliant

### Applications

- DC Motor Drive and BMS industrial application.
- Synchronous Rectification in DC/DC and AC/DC Converters

### Product Summary


$V_{DS}$	80V
$I_D$ (at $V_{GS}=10V$ )	268A
$R_{DS(ON)}$ (at $V_{GS}=10V$ )	< 1.8mΩ
$R_{DS(ON)}$ (at $V_{GS}=8V$ )	< 2mΩ

100% UIS Tested  
100%  $R_g$  Tested



Max  $T_j=175^\circ C$



**TOLLA**



**Bottom View**



Orderable Part Number	Package Type	Form	Minimum Order Quantity
AOTL66811	TOLLA	Tape & Reel	2000

### Absolute Maximum Ratings $T_A=25^\circ C$ unless otherwise noted

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	$V_{DS}$	80	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current	$I_D$	268	A
$T_C=100^\circ C$		190	
Pulsed Drain Current <sup>C</sup>	$I_{DM}$	650	
Continuous Drain Current	$I_{DSM}$	50	A
$T_A=70^\circ C$		43	
Avalanche Current <sup>C</sup>	$I_{AS}$	67	A
Avalanche energy $L=0.1mH$ <sup>C</sup>	$E_{AS}$	224	mJ
Power Dissipation <sup>B</sup>	$P_D$	272	W
$T_C=100^\circ C$		136	
Power Dissipation <sup>A</sup>	$P_{DSM}$	10	W
$T_A=70^\circ C$		7	
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 175	°C

### Thermal Characteristics

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient <sup>A</sup> $t \leq 10s$	$R_{0JA}$	10	15	°C/W
Maximum Junction-to-Ambient <sup>A,D</sup> Steady-State		35	45	°C/W
Maximum Junction-to-Case	$R_{0JC}$	0.35	0.55	°C/W

**Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
$BV_{DSS}$	Drain-Source Breakdown Voltage	$I_D=250\mu\text{A}, V_{GS}=0\text{V}$	80			V
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS}=80\text{V}, V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$		1	5	$\mu\text{A}$
$I_{GSS}$	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS}=\pm20\text{V}$			$\pm100$	nA
$V_{GS(\text{th})}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	2.5	3.2	3.8	V
$R_{DS(\text{ON})}$	Static Drain-Source On-Resistance	$V_{GS}=10\text{V}, I_D=20\text{A}$ $T_J=125^\circ\text{C}$		1.5	1.8	$\text{m}\Omega$
		$V_{GS}=8\text{V}, I_D=20\text{A}$		2.4	3	$\text{m}\Omega$
$g_{FS}$	Forward Transconductance	$V_{DS}=5\text{V}, I_D=20\text{A}$		90		S
$V_{SD}$	Diode Forward Voltage	$I_S=1\text{A}, V_{GS}=0\text{V}$		0.7	1	V
$I_S$	Maximum Body-Diode Continuous Current				200	A
<b>DYNAMIC PARAMETERS</b>						
$C_{iss}$	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=40\text{V}, f=1\text{MHz}$		7680		pF
$C_{oss}$	Output Capacitance			2130		pF
$C_{rss}$	Reverse Transfer Capacitance			45		pF
$R_g$	Gate resistance	$f=1\text{MHz}$	1.1	2.3	3.5	$\Omega$
<b>SWITCHING PARAMETERS</b>						
$Q_g(10\text{V})$	Total Gate Charge	$V_{GS}=10\text{V}, V_{DS}=40\text{V}, I_D=20\text{A}$		102	145	nC
$Q_{gs}$	Gate Source Charge			27		nC
$Q_{gd}$	Gate Drain Charge			21		nC
$Q_{oss}$	Output Charge	$V_{GS}=0\text{V}, V_{DS}=40\text{V}$		152		nC
$t_{D(\text{on})}$	Turn-On DelayTime	$V_{GS}=10\text{V}, V_{DS}=40\text{V}, R_L=2\Omega, R_{\text{GEN}}=3\Omega$		24		ns
$t_r$	Turn-On Rise Time			16		ns
$t_{D(\text{off})}$	Turn-Off DelayTime			72		ns
$t_f$	Turn-Off Fall Time			21		ns
$t_{rr}$	Body Diode Reverse Recovery Time	$I_F=20\text{A}, di/dt=500\text{A}/\mu\text{s}$		40		ns
$Q_{rr}$	Body Diode Reverse Recovery Charge	$I_F=20\text{A}, di/dt=500\text{A}/\mu\text{s}$		233		nC

A. The value of  $R_{iJA}$  is measured with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The Power dissipation  $P_{DSM}$  is based on  $R_{iJA} \leq 10\text{s}$  and the maximum allowed junction temperature of  $175^\circ\text{C}$ . The value in any given application depends on the user's specific board design, and the maximum temperature of  $175^\circ\text{C}$  may be used if the PCB allows it.

B. The power dissipation  $P_D$  is based on  $T_{J(\text{MAX})}=175^\circ\text{C}$ , using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Single pulse width limited by junction temperature  $T_{J(\text{MAX})}=175^\circ\text{C}$ .

D. The  $R_{iJA}$  is the sum of the thermal impedance from junction to case  $R_{iJC}$  and case to ambient.







E. The static characteristics in Figures 1 to 6 are obtained using <300μs pulses, duty cycle 0.5% max.






F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of  $T_{J(\text{MAX})}=175^\circ\text{C}$ . The SOA curve provides a single pulse rating. .

G. These tests are performed with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ .

APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO MAKE CHANGES TO PRODUCT SPECIFICATIONS WITHOUT NOTICE. IT IS THE RESPONSIBILITY OF THE CUSTOMER TO EVALUATE SUITABILITY OF THE PRODUCT FOR THEIR INTENDED APPLICATION. CUSTOMER SHALL COMPLY WITH APPLICABLE LEGAL REQUIREMENTS, INCLUDING ALL APPLICABLE EXPORT CONTROL RULES, REGULATIONS AND LIMITATIONS.

AOS' products are provided subject to AOS' terms and conditions of sale which are set forth at:  
[http://www.aosmd.com/terms\\_and\\_conditions\\_of\\_sale](http://www.aosmd.com/terms_and_conditions_of_sale)

**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**

**Figure 1: On-Region Characteristics (Note E)**

**Figure 2: Transfer Characteristics (Note E)**

**Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)**

**Figure 4: On-Resistance vs. Junction Temperature (Note E)**

**Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)**

**Figure 6: Body-Diode Characteristics (Note E)**

**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**







**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**

**Figure 12: Power De-rating (Note F)**

**Figure 13: Current De-rating (Note F)**

**Figure 14: Coss stored Energy**

**Figure 15: Single Pulse Power Rating Junction-to-Ambient (Note G)**

**Figure 16: Normalized Maximum Transient Thermal Impedance (Note G)**

Figure A: Gate Charge Test Circuit & Waveforms




Figure B: Resistive Switching Test Circuit & Waveforms




Figure C: Unclamped Inductive Switching (UIS) Test Circuit & Waveforms




Figure D: Diode Recovery Test Circuit & Waveforms

