

ESD TEST REPORT

Human Body Model

JS-001-2017

ANSI/ESDA/JEDEC Standard, Method JS-001-2017 is an ESD test using Human Body Model where "R = 1500 ohm", "C = 100pf", one positive and one negative pulses applied to the devices per customer's specification with a minimum of 0.1 second cool down between pulses.

Customer : Alpha & Omega Semiconductor (Shanghai), Ltd.

Address: Building 8 & 9, No. 91, Lane 109, Rong Kang Road,
Songjiang Export Processing Zone, Zone B, # 888 Song Zheng Highroad, Shanghai

Device Information

Part No. :	AOCA33103E	Sample Size :	8pcs
Package Type :	AlphaDFN2.52X2.52_10L	Pin Count :	10
Lot No. :	BA00(K1401)	Date Code :	-
VDD Domains :	S2 S1	VSS Domains :	S1 S2

Test Equipment

Tester :	ZAPMASTER MK.2 SE	Serial No. :	0508317
Calibration Date :	Jan 14 th 2021	Expiration Date :	Jan 13 th 2022

Environmental Condition

Temperature :	23°C	Humidity :	50% RH
Submit date :	May 20 th 2021	Complete date :	May 24 th 2021

Stress Summary

Channel_1 G1 TO S1			
Sample No.	Stress Type	Voltage Level	Spot Test Results* (Within 10μA @ 8V between G1 and S2/S1)
1#	HBM	+5.1kV	FAILED
2#	HBM	±5kV	PASS
3#	HBM	±5kV	PASS
4#	HBM	±5kV	PASS

Channel_1 G1 TO S2			
Sample No.	Stress Type	Voltage Level	Spot Test Results* (Within 10μA @ 8V between G1 and S2/S1)
5#	HBM	-5kV	FAILED
6#	HBM	±4.9kV	PASS
7#	HBM	±4.9kV	PASS
8#	HBM	±4.9kV	PASS


Channel_2 G2 TO S2			
Sample No.	Stress Type	Voltage Level	Spot Test Results* (Within 10μA @ 8V between G2 and S1/S2)
1#	HBM	+5.2kV	FAILED
2#	HBM	±5.1kV	PASS
3#	HBM	±5.1kV	PASS
4#	HBM	±5.1kV	PASS

Channel_2 G2 TO S1			
Sample No.	Stress Type	Voltage Level	Spot Test Results* (Within 10µA @ 8V between G2 and S1/S2)
5#	HBM	+5.1kV	FAILED
6#	HBM	±5kV	PASS
7#	HBM	±5kV	PASS
8#	HBM	±5kV	PASS

Test Result*

Model	Pin Combinations	ESD Sensitivity Pass*: <u>4.9kV</u>	V Class
HBM	Channel 1 – G1 vs. S1	±5kV	3A JS-001-2017 Class 0Z: <50V Class 0A: 50V~124V Class 0B: 125V~249V Class 1A: 250V~499V Class 1B: 500V~999V Class 1C: 1000V~1999V Class 2: 2000V~3999V Class 3A: 4000V~7999V Class 3B: ≥8000V
	Channel 1 – G1 vs. S2	±4.9kV	
	Channel 2 – G2 vs. S2	±5.1kV	
	Channel 2 – G2 vs. S1	±5kV	

*Note: Results will be updated based on customer final electrical test results.

Test Engineer: Wenping Yan	Date: May 24 th 2021
Approved by FA Manager: 	Date: May 24 th 2021



Recommendations

EAG Shanghai certifies that above tests have been performed in accordance to the requirements stated above and per the customer purchase order and applicable documents.

EAG Shanghai recommends electrical testing as a validation of reported results. Curve Trace criteria was utilized to specify a pass or fail. Industry standards require the device to be tested functionally at post stress and should continue to meet all electrical parameters as per the data sheet.

This report can not be duplicated in part, without the permission of EAG Shanghai. This report refers only to the specimen(s) submitted to test, and is invalid if used separately. This report is only valid with the examination seal and signature of EAG Shanghai. The tested specimen(s) will only be preserved for thirty days form the date issued, if not collected by the applicant. If discrepancies exist about report, please put forward within one week.